



## ACCESSORIES

## 103 GUARD TUBE



Reference	Dimensions (mm)	Conductor range			Included	Material	Weight (kg)
		Ø(mm)	mm <sup>2</sup>	Tape (mm)			
AT-051G	Ø27 x 2000	8 – 10	50 – 70	-	Bonding clamps	Galvanized steel	3
AT-050G	Ø27 x 3000	8 – 10	50 – 70	-	Bonding clamps	Galvanized steel	5
AT-053G	Ø27 x 2000	8 – 10	50 – 70	-	Bonding clamps	Stainless steel	2,3
AT-054G	Ø27 x 3000	8 – 10	50 – 70	-	Bonding clamps	Stainless steel	3,5
AT-060G	40 x 14 x 2000	-	-	30x2 – 30x3,5	Bonding clamps	Galvanized steel	1
AT-055G	70 x 15 x 2000	8 – 10	50 – 70	30x2 – 30x3,5	Plug and screw	Galvanized steel	3
AT-057G	40 x 30 x 1500	7 – 10	35 – 70	-	Straight clamp and KS cable clip	Galvanized steel	2,6

Meets with BS 1449-1, BS 970, AS 1397, UNE 21186, NFC 17102



Anti vandal guard for round or tape down-conductors. In order to avoid the break of the cable by accidental impacts, it is necessary to install a guard tube, at least 2 meter high, wherever the cable is accessible.

